



MATERIAL SAFETY DATA SHEET

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

IDENTITY

APC Precision Colored Hardener (All Colors)

SECTION - MANUFACTURER

Alabama Pigments Company, LLC.
346 Rickey Road
McCalla, AL 35111

Emergency Contact
800-531-1172
Information Contact
205-938-3065

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

<u>Components</u>	<u>%</u>	<u>OSHA-PEL</u>	<u>ACGIH-TLV</u>
Mineral Filler	10-20	5mg/m ³	15mg/m ³
Free SiO ₂	2	10mg/m ³	5mg/m ³

None of the components of the mixture are considered Hazardous Material or carcinogens (1910.1200 Hazard Communication (d)[4]).

TRANSPORTATION INFORMATION

DOT Classification: NA

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Not know to boil	Specific Gravity(520=1): 2.2
Vapor Pressure: NA	Melting Point:NA
Vapor Density (Air=1): NA	Evaporation:NA
Solubility in Water: Negligible	
Appearance: Varies depending on color ordered .	

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point (Tag Closed Cup): NA
Flammable Limits: NA

SECTION V - REACTIVITY DATA

Stability : Stable
Incompatibility: None
Hazardous Decomposition (By-products): None
Hazardous Polymerization: Will not occur.

SECTION VI – HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Inhalation? Yes

Skin? Yes

Eyes? Yes

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE

Acute: Nuisance Dust

Chronic: No chronic health effects are known from repeated exposure to iron oxide pigments.

Medical Conditions: Aggravated by Exposure: None Known.

Carcinogenicity: Not applicable

EXPOSURE LIMITS

OSHA PEL: Not established for this product

ACGIH TLV: Not established of the product. The recommended guideline is the TLV for nuisance particulates, 10mg/m³ of total dust.

EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Flush eye with plenty of water, lifting lids periodically for at least 15 minutes. Consult a physician if irritation persists.

Skin Contact: Wash with soap and water.

Inhalation: Remove form dusty area to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion: Immediately contact a physician.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Common housekeeping, vacuum or scoop material into a container for reclamation or disposal.

Waste Disposal Method: Material that cannot be reclaimed should be landfilled in accordance with local, state, and federal regulations.

Precautions to be Taken in Handling and Storing: Store in dry area. Material should be kept dry. Avoid breathing dust. Avoid contact with eyes and skin. Wash thoroughly after handling.

Other Precautions: None

SECTION VIII – CONTROL MEASURES

Respiratory Protection: NIOSH approved dust respirator when required for dust.

Ventilation: Observe EPA standards

Protective Gloves: For Sensitive Skin

Protective Glasses: Safety goggles or face shield to protect against accidental splashes

Other Protective Clothing or Equipment: Safety showers and eye wash stations should be available.

Work/Hygiene Practices: Wash thoroughly with soap and water before eating, smoking or using washroom. Remove and wash contaminated clothing before re-use.

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, Alabama Pigments Company, LLC. Makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Alabama Pigments Company, LLC. Be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, wither express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers.

Alabama Pigments Company, LLC.

Date 4/2006