



Alabama Pigments Company, LLC.

PRECISION CLEAR SEAL-30

PRODUCT NAME: APC Precision Clear Seal-30
PRODUCT CODE: CE-36 or CE-30

HMIS CODES H F R P*
2 2 0
* SEE SECTION X

Section I - Distributor Identification

DISTRIBUTOR'S NAME: Alabama Pigments Company, LLC.
ADDRESS: 346 Rickey Road
McCalla, AL 35111

EMERGENCY PHONE: 800-531-1172 **Date Printed:** 10/11/2007
INFORMATION PHONE: 205-938-3065

Section II - Hazardous Ingredients/Sara III Information

Reportable Components	CAS Number	Vapor Pressure mm Mg @ TEMP	Weight Percent
SOLVENT 100 PEL 100 PPM	64742-95-6	2.10mmHG	83.71

Indicates a hazardous air pollutant (HAP) subject to EPA Section 112 reporting.
* Indicates a toxic chemical subject to Section 313 of Title III and 40 CFR 372 reporting.

Section III - Physical/Chemical Characteristics

BOILING RANGE: N/A **SPECIFIC GRAVITY (H2O=1):** 0.89
VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SOLVENTS WILL
EVAPORATE SLOWER THAN ETHER
COATING V.O.C.: 6.20 lb/gl **MATERIAL V.O.C.:** 6.20 lb/gl
SOLUBILITY IN WATER: NEGLIGIBLE
APPEARANCE AND ODOR: LIQUID WITH SOLVENT ODOR

Section IV - Fire and Explosive Hazard Data

FLASH POINT: 110 F **METHOD USED:** TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- **LOWER:** 1% (V) **UPPER:** 7% (V)

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite if solvent vapors are still present.

Section V - Reactivity Data

STABILITY: Stable

CONDITIONS TO AVOID

Excessive heat, poor ventilation, corrosive atmosphere, excessive aging.

INCOMPATIBILITY (MATERIALS TO AVOID)

Alkaline materials, strong acids and oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Under combustion conditions will yield oxides of carbon, carbon monoxide and carbon dioxide or other toxic fumes resulting from nitrogen or chlorine.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

Section VI - Health Hazard Data

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eyes - Can cause severe irritation, redness, tearing, blurred vision.

Skin- May cause skin irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Prolonged or repeated contact or exposure to vapors or mists may cause redness, burning, drying and cracking of the skin

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. If swallowed, do not induce vomiting. Keep person warm, quiet, and get medical attention.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPH'S: NO OSHA REGULATED: YES

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: If breathed, if affected, move individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Keep person warm, quiet and get medical attention.

EYES: If in eyes, flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.

SKIN: If on skin, thoroughly wash exposed area with soap and water. Remove contaminated clothing and laundry or dispose of.

INGESTION: If swallowed, do not induce vomiting. Keep person warm, quiet, and get medical attention.

Section VII - Precautions for Safe Handling and Use

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL RELEASE: Absorb material with vermiculite, floor absorbent, or other absorbent material and transfer to HOOD.

LARGE SPILL: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until cleanup has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

WASTE DISPOSAL METHOD- Dispose of in accordance with all federal, state and local regulations

Section VII - Precautions for Safe Handling and Use (Cont)

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Use non-sparking utensils when handling this material. Avoid hot metal surface. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

OTHER PRECAUTIONS

We recommend that containers be either professionally reconditioned for reuse by certified firms or properly disposed of by certified firms to help reduce the possibility of an accident. Disposal of containers should be in accordance with applicable federal, state and local laws and regulations. "Empty" drums or pails should not be given to individuals.

Section VIII - Control Measures

RESPIRATORY PROTECTION

If TLV of the product or any component is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators under specified conditions (See you safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure

VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES

Wear chemical resistant gloves.

EYE PROTECTION

Chemical splash goggles in compliance with OSHA regulations are advised. However OSHA regulations also permit other type safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use impermeable aprons and protective clothing and footwear whenever possible to prevent skin contact.

WORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended

Section IX - Disclaimer

The information on this material safety data sheet is believed to be accurate but is not warranted to be so. Protective equipment, health effects, and other related safety measures are based on intended and anticipated product use. Recipients are advised to confirm, in advance of need that the information is applicable and suitable to their circumstances.

Section X - Additional Information

*** PERSONAL PROTECTION RATING TO BE SUPPLIED BY USER DEPENDING ON USE CONDITIONS.**

HMIS (NPCA)

HAZARD RANKING

HEALTH

0 = LEAST

FLAMMABILITY

1 = SLIGHT

REACTIVITY

2 = MODERATE

PERSONAL PROTECTION

3 = HIGH

4 = EXTREME